

SAFETY DATA SHEET BELZONA® 7111 BASE

SECTION 1: Identification: Product identifier and chemical identity

Product identifier

Product name BELZONA® 7111 BASE

Product No. SN2816, SN2829

Relevant identified uses of the substance or mixture and uses advised against

Application A chocking or grouting material designed to endure the physical and thermal shock common

to marine and industrial environments. For industrial use only.

appropriate Instructions For Use (IFU) leaflet.

Details of the supplier of the safety data sheet

Supplier Rezitech Services Reptech Corporation Ltd

9 Southfork Drive 503 Great South Road Kilsyth 3137, Victoria Penrose, Auckland 1061

AUSTRALIA NEW ZEALAND

+44 1423 567641 0800 (REPTECH) 737832

Manufacturer Belzona Inc.

14300 NW 60th Ave.

Miami Lakes FL 33014 USA

1-305-594-4994 sds@belzona.com

Emergency telephone number

Emergency telephone Australia: Steven Hunt +61 404 843 835

New Zealand: National Poisons Centre 0800 764 766

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Hazard pictograms





Signal word WARNING

BELZONA® 7111 BASE

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P280 Wear protective clothing, gloves, eye and face protection.

P273 Avoid release to the environment.

P333+P313 If skin irritation or rash occurs: Get medical attention.

P363 Wash contaminated clothing before reuse.

P337+P313 If eye irritation persists: Get medical attention.

P391 Collect spillage.

Contains EPOXY RESIN (Number average MW <= 700), EPOXY PHENOL NOVOLAC RESIN

Other hazards

HSNO classification: 6.3A 6.4A 6.5B 9.1B

SECTION 3: Composition and information on ingredients

Mixtures

EPOXY RESIN (Number average MW <= 700)

30-60%

CAS number: 25085-99-8

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

EPOXY PHENOL NOVOLAC RESIN

1-5%

CAS number: 9003-36-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

Description of first aid measures

General information In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything

by mouth to an unconscious person.

Inhalation Remove to fresh air. Keep the patient warm and at rest. Give nothing by mouth.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Rinse mouth with

plenty of water. Do NOT induce vomiting.

Skin Contact Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

proprietary skin cleaner. Do NOT use solvents or thinners. If irritation or inflammation

persists, seek medical attention.

Eye contact Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15

minutes, holding the eyelids apart, and seek medical advice.

BELZONA® 7111 BASE

Most important symptoms and effects, both acute and delayed

Inhalation Vapours may irritate throat/respiratory system.

Inadvertent ingestion of small amounts of this product through poor hygiene or cross

contamination may cause irritation of mucous membranes.

Skin contact Causes skin irritation. Prolonged or repeated contact with the skin or mucous membrane may

result in irritant symptoms such as redness, blistering or dermatitis. Onset of symptoms may

be delayed. May cause allergic skin reaction.

Eye contact Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor None.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media Use: sand, alcohol resistant foam, carbon dioxide, chemical powder, or water fog for larger

fires

Do NOT use water jet.

Special hazards arising from the substance or mixture

Hazardous combustion Thermal decon

products

Thermal decomposition or combustion products may include the following substances:

Phenolic. Carbon monoxide (CO). Carbon dioxide (CO2).

Advice for firefighters

Protective actions during

firefighting

Fire will produce dense black smoke containing hazardous products of combustion. Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not

allow run-off from fire fighting to enter drains or watercourses.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Exclude

non-essential personnel. Exclude sources of ignition and ventilate the area. Keep up-wind of

spill to avoid breathing vapours. Avoid contact with skin and eyes.

Environmental precautions

Environmental precautions Prevent product entering drains or sewers. If the product enters drains or sewers in large

quantities, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the appropriate National regulating agency.

Methods and material for containment and cleaning up

Methods for cleaning up Scrape the majority of the product into a suitable labelled container. Cover the spill area with

sand or other suitable inert material and sweep up into the container. Clean surfaces down with a water and detergent mixture. Do not allow spilled product or the associated washings to

enter surface water drains or watercourses.

Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13. .

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

BELZONA® 7111 BASE

Usage precautions

GENERAL Keep the container tightly closed when not in use. Vapours may collect in the container headspace during transit or prolonged storage. Avoid the inhalation of vapour when opening the container. Where possible open containers and mix components in a well ventilated place away from the application area. Prevent air-borne concentrations higher than the occupational exposure limits (see Section 8). Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Always keep in containers made of the same material as the supply container. Good housekeeping methods and regular safe removal of waste materials should be observed. The Manual Handling Operations Regulations may apply to the handling of containers/packages of this product. Refer to the guide weight on the container/package when carrying out assessments. FIRE/EXPLOSION This product is combustible. Exclude sources of heat, sparks and open flame. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards. Ensure emergency equipment (for fires, spills, leaks, etc.) is readily available.

Conditions for safe storage, including any incompatibilities

Storage precautions

Observe the label precautions. Store between 5 °C and 30 °C unless otherwise stated in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. ENVIRONMENTAL STORAGE PRECAUTIONS Spillage, incorrect storage of chemicals or waste materials or unsuitable disposal activities can result in pollutants seeping through the soil, causing serious harm to groundwater- which is a vital source of drinking water. All wastes, especially liquid wastes, must be securely stored on site in designated areas that are isolated from surface drains and bunded to contain any spillages.

Specific end use(s)

Specific end use(s)

Application by pouring. Mix with Solidifier component before use. Please refer to the relevant Belzona® Instructions For Use for further information.

SECTION 8: Exposure controls and personal protection

Ingredient comments

When personal protective equipment, including respiratory protective equipment, is used to control exposure to hazardous substances it must be selected to meet the requirements of the COSHH Regulations. OEL's are taken from the current version of EH40 except those that are marked 'SUP' which are assigned by the supplier of the substance. Exposure to chemicals assigned occupational exposure limits (OELs) should be controlled using the most effective and reliable measures, proportional to the health risk, which minimise their escape and spread. All relevant exposure routes should be taken into account.

Exposure controls

Appropriate engineering controls

Use in well ventilated areas or provide adequate mechanical ventilation. If these are not sufficient to maintain concentrations of vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see 'Respiratory protection' below).

Eye/face protection

It is recommended that eye protection, for example safety spectacles or goggles are worn at all times during the handling and use of this material. Eye protection should be selected in accordance with EN 166 Personal eye protection. During subsequent machining, grinding, abrasion or removal of this product appropriate eye protection should be selected according to the type of tools or equipment used.

BELZONA® 7111 BASE

Hand protection

Hand protection should be selected in accordance with EN 374 Protective gloves against chemicals. The breakthrough time of the gloves selected should exceed the expected use period. Where this is not possible gloves should be changed in good time, and in any case before the breakthrough time is exceeded. If any doubt exists, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred. SPECIFIC RECOMMENDATIONS Wear protective gloves made of the following material: Nitrile. Medium-heavy weight gauntlet type gloves that provide wrist protection are suitable.

Other skin and body

protection

STANDARD APPLICATIONS Synthetic polyethylene coveralls such as the Tyvek PRO-TECH® or equivalent coveralls manufactured to EN 13034 Type 6, Protective clothing against liquid chemicals. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Ensure eye wash facilities (fountain, bottle, vials, etc.) are readily available. Do not put contaminated articles or equipment e.g. spatulas, applicators, brushes, cloths etc., into pockets. Where necessary, contaminated work clothing and shoes should be removed to prevent cross contamination of surfaces and the risk of inadvertent skin contact and ingestion.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. It is essential that the concentration of the contaminant(s) in the application environment does not exceed the applicable Occupational Exposure Limit(s) (OELs) multiplied by the Assigned Protection Factor (APF) quoted for the respiratory protective equipment selected. STANDARD APPLICATIONS Respiratory protection is not normally required, but the hazards of the Solidifier component should be considered for mixing and application purposes.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance Paste.

Colour Orange. Light grey.

Odour Epoxy.

Odour threshold Not available.

pH Not applicable.

Melting point Not available.

Initial boiling point and range Not available.

Flash point > 93°C/199°F Estimated value.

Not available.

Evaporation rateNot available.Flammability (solid, gas)Not applicable.Flammability Limit - Lower(%)Not available.

Vapour density >1

Vapour pressure

Relative density 1.62 @ 25°C/77°F

Solubility(ies) Insoluble in water.

BELZONA® 7111 BASE

Partition coefficientNot available.Auto-ignition temperatureNot available.Decomposition TemperatureNot available.ViscosityNot available.

Explosive properties Not applicable.

Oxidising properties Not applicable.

Other information This section contains typical values for Health, Safety and Environmental guidance only and is

not intended to represent a technical specification for the product.

SECTION 10: Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stability Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous

reactions

No hazardous reactions expected when stored and handled as recommended.

Conditions to avoid Avoid inadvertent contamination with water/moisture.

Materials to avoid Avoid contact with the following materials: Oxidising agents. Amines. Acids. Alkalis. Water,

moisture.

Hazardous decomposition

products

Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD50) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on the properties of the epoxy constituent(s) and considering toxicological data on

similar preparations, this preparation may be a skin sensitiser. Repeated skin contact may

lead to sensitisation with possibly cross-sensitisation to other epoxies.

Germ cell mutagenicity

BELZONA® 7111 BASE

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Not listed.

NTP carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Route of exposure Inhalation Ingestion Skin and/or eye contact

Medical considerations Skin contact constitutes a pronounced hazard. Persons with a history of skin sensitisation

problems should only be employed in processes in which this product is used under

appropriate medical supervision.

SECTION 12: Ecological information

Ecotoxicity There is no data on the product itself. The following information is provided on the basis of the

individual component data available.

Toxicity Based on the epoxy resin content, this product is expected to have experimental

LC50/EC50/IC50 values between 1 and 10 mg/l in most sensitive species.

Persistence and degradability

Persistence and degradability Based on the epoxy resin content, this product is not expected to be rapidly biodegradable

according to OECD/EC guidelines.

Bioaccumulative potential

Bioaccumulative Potential Based on the epoxy resin content, this product is expected to bioaccumulate.

Partition coefficient Not available.

Mobility in soil

Mobility There is no data available on the product itself.

Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

Waste treatment methods

BELZONA® 7111 BASE

General information

All cleaning activities including cleaning of equipment, floors and containers, can produce large volumes of contaminated waste. All cleaning agents used are potentially polluting. Water containing detergents, degreasers or any other cleaning agents must not be allowed to enter the surface water drains or soakaways. All water based cleaning/degreasing operations should be carried out in designated areas away from the surface water system and drained to the foul water system. Where this is not possible the surface water system should be isolated by suitable damming techniques and the contaminated water collected and removed for controlled safe disposal. Where water immiscible cleaners/degreasers are used for example solvents, the relevant product safety data sheet should be referred to for information on safe disposal.

Disposal methods

GENERAL Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled wastes include non-hazardous industrial and hazardous chemical wastes. All controlled wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. In addition, hazardous chemical wastes should be disposed of in accordance with the Hazardous Waste Regulations. When in doubt, using information provided in this safety data sheet, advice should be obtained from the National regulating agency whether the Hazardous Waste Regulations apply. Refer to information sources listed in Section 16. COMPONENT DISPOSAL TRANSIT PACKAGING: shrink or stretch wrap, boxes and fittings that have not been contaminated with product should be re-used or recycled. UNREACTED PRODUCT and empty uncleaned containers should be disposed of as hazardous chemical waste. REACTED PRODUCT, contaminated mixing boards, spatulas, applicators, brushes, nominally empty containers and mixing bowls- once fully cured- should be disposed of as non-hazardous waste.

Waste class

. *Hazardous waste pursuant to Directive 91/689/EEC. The LoW code quoted in this section is a general entry. LoW codes should be assigned based on the end use of the product. Where a more specific code is available it should be used in preference to the code given above. Where in doubt refer to the List of Wastes (2000/532/EC Comission Decision), your local licensed waste contractor or the National regulating agency. Refer to information sources listed in Section 16.

SECTION 14: Transport information

General Labelling and packaging requirements may vary with pack and load size. Please refer to the

current transport regulations. Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know

what to do in the event of accident or spillage.

UN number

UN No. (ADG) 3082 UN No. (IMDG) 3082 UN No. (ICAO) 3082

UN proper shipping name

Proper shipping name (ADG) Environmentally hazardous substance, liquid, n.o.s. (containing Epoxy resin mixture)

Proper shipping name (IMDG)

Environmentally hazardous substance, liquid, n.o.s. (containing Epoxy resin mixture)

Proper shipping name (ICAO) Environmentally hazardous substance, liquid, n.o.s. (containing Epoxy resin mixture)

Transport hazard class(es)

ADG class 9

BELZONA® 7111 BASE

IMDG class 9

ICAO class/division 9

Packing group

ADG packing group III
IMDG packing group III
ICAO packing group III

Environmental hazards

Environmentally hazardous substance/marine pollutant



Labelling requirements will vary with hazardous net quantity. Please refer to the current transport regulations.

Special precautions for user

Not applicable.

Transport in bulk according to Not carried in bulk.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations GROUP STANDARD: Surface coatings and colourants (Subsidiary)

HSNO APPROVAL NUMBER: HSR002670

Inventories

Australia - AICS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

General information The information contained within this safety data sheet does not constitute the users own

assessment of workplace risks as required by other health and safety legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant National legislation are complied with. The information contained within this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of

technical performance or suitability for particular applications.

Key literature references and sources for data

Revision comments

.

Training advice For further information please contact your supplier, Belzona consultant or Belzona direct.

REVISION. This safety data sheet has been revised in the following Section(s): 5, 8, Please observe the REVISION DATE. Should you be reading a safety data sheet that is more than 24 months old or have concerns over its validity, please contact your local Belzona consultant or Belzona direct (sds@belzona.com) and the most current information will be sent to you.

BELZONA® 7111 BASE

Revision date 5/01/2021

Revision 7.2

SDS No. 40977

SDS status English. Approved.

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.